## Weather Shield®

## **Push-Out Casement Windows**

## Premium Coastal Series™

**Elevation Details** 

Push-Out Casements	(1214)	Insulated	Glass

Ja	mb	Dir	mer	nsion	1'-5 1/2"	1'-7 1/2"	1'-11 1/2"	2'-3 1/2"	2'-5 1/2"	2'-7 1/2"	2'-11 1/2"
				pening	1'-6"	1'-8"	2'-0"	2'-4"	2'-6"	2'-8"	3'-0"
				c R.O. (mm)	457	508	610	711	762	813	914
				ass Size	12 3/4"	14 3/4"	18 3/4"	22 3/4"	24 3/4"	26 3/4"	30 3/4"
1'-11 1/2"	20	610	18 3/4"								
2'-5 1/2"	2'-6"	762	24 3/4"		1620	1820	2020	2420	2620	2820	3020
2'-11 1/2"	30	914	30 3/4"		1626	1826	2026	2426	2626	2826	3026
3'-5 1/2"	3'-6"	1067	36 3/4"		1630	1830	2030	2430	2630	2830	3030
3'-11 1/2"	4'-0"	1219	42 3/4"		1636	1836	2036	2436	2636	2836	3036
4'-5 1/2"	4'-6"	1372	48 3/4"		1640	1840	2040	2440	2640	2840	3040
4'-11 1/2"	20	1524	54 3/4"		1646	1846	2046	2446	2646	2846	3046
	.9	9,	3/4"		1650	1850	2050	2450	2650	2850	3050
5'-5 1/2"	19-19	1676	60 3/4"		1656	1856	2056	2456	2656	2856	3056
5'-11 1/2"	0-,9	1829	66 3/4"		1660	1860	2060	2460	2660	2860	3060
6'-5 1/2"	.9-,9	1981	72 3/4"								
					1666	1866	2066	2466	2666	2866	3066

Shaded units meet or exceed egress opening requirements per 2015 IBC (International Building Code) minimum dimensions of 20" [508mm] clear opening width, 24" [610mm] clear opening height, 5.7 sq. ft. [5295cm²] clear opening and floor to bottom of clear opening not to exceed 44" [1118mm] in height.

Verify local or state egress opening sizes with your local building inspector.

Floor to bottom of clear opening dimensions are based on 82" [2083mm] jamb height of Weather Shield French doors and center hinged French doors.

See Opening Specification chart for reference.