


Eyebrow Casement Windows (8211) / Push-Out Casements (8217)^{*up to 7-0 only - 1 Wide}

Jamb Dimension	1'-11 1/2"	2'-3 1/2"	2'-5 1/2"	2'-7 1/2"	2'-11 1/2"	3'-5 1/2"
Rough Opening	2'-0"	2'-4"	2'-6"	2'-8"	3'-0"	3'-6"
Metric R.O. (mm)	610	711	762	813	914	1067
Glass Size	18 3/4"	22 3/4"	24 3/4"	26 3/4"	30 3/4"	36 3/4"
Jamb Radius	24"	24"	30"	30"	36"	40"
Jamb Leg Drop	3 1/16"	4 5/16"	3 7/8"	4 7/16"	4 11/16"	5 13/16"

2'-11 1/2"	2'-11 1/2"	2'-11 1/2"	2'-11 1/2"	2'-11 1/2"	2'-11 1/2"	2'-11 1/2"
3'-0"	3'-0"	3'-0"	3'-0"	3'-0"	3'-0"	3'-0"
914	914	914	914	914	914	914
30 3/4"	30 3/4"	30 3/4"	30 3/4"	30 3/4"	30 3/4"	30 3/4"
2030	2430	2630	2830	3030	3630	
3'-5 1/2"	3'-5 1/2"	3'-5 1/2"	3'-5 1/2"	3'-5 1/2"	3'-5 1/2"	3'-5 1/2"
3'-6"	3'-6"	3'-6"	3'-6"	3'-6"	3'-6"	3'-6"
1067	1067	1067	1067	1067	1067	1067
36 3/4"	36 3/4"	36 3/4"	36 3/4"	36 3/4"	36 3/4"	36 3/4"
2036	2436	2636	2836	3036	3636	
3'-11 1/2"	3'-11 1/2"	3'-11 1/2"	3'-11 1/2"	3'-11 1/2"	3'-11 1/2"	3'-11 1/2"
4'-0"	4'-0"	4'-0"	4'-0"	4'-0"	4'-0"	4'-0"
1219	1219	1219	1219	1219	1219	1219
42 3/4"	42 3/4"	42 3/4"	42 3/4"	42 3/4"	42 3/4"	42 3/4"
2040	2440	2640	2840	3040	3640	
4'-5 1/2"	4'-5 1/2"	4'-5 1/2"	4'-5 1/2"	4'-5 1/2"	4'-5 1/2"	4'-5 1/2"
4'-6"	4'-6"	4'-6"	4'-6"	4'-6"	4'-6"	4'-6"
1372	1372	1372	1372	1372	1372	1372
48 3/4"	48 3/4"	48 3/4"	48 3/4"	48 3/4"	48 3/4"	48 3/4"
2046	2446	2646	2846	3046	3646	
4'-11 1/2"	4'-11 1/2"	4'-11 1/2"	4'-11 1/2"	4'-11 1/2"	4'-11 1/2"	4'-11 1/2"
5'-0"	5'-0"	5'-0"	5'-0"	5'-0"	5'-0"	5'-0"
1524	1524	1524	1524	1524	1524	1524
54 3/4"	54 3/4"	54 3/4"	54 3/4"	54 3/4"	54 3/4"	54 3/4"
2050	2450	2650	2850	3050	3650	
5'-5 1/2"	5'-5 1/2"	5'-5 1/2"	5'-5 1/2"	5'-5 1/2"	5'-5 1/2"	5'-5 1/2"
5'-6"	5'-6"	5'-6"	5'-6"	5'-6"	5'-6"	5'-6"
1676	1676	1676	1676	1676	1676	1676
60 3/4"	60 3/4"	60 3/4"	60 3/4"	60 3/4"	60 3/4"	60 3/4"
2056	2456	2656	2856	3056	3656	
5'-11 1/2"	5'-11 1/2"	5'-11 1/2"	5'-11 1/2"	5'-11 1/2"	5'-11 1/2"	5'-11 1/2"
6'-0"	6'-0"	6'-0"	6'-0"	6'-0"	6'-0"	6'-0"
1829	1829	1829	1829	1829	1829	1829
66 3/4"	66 3/4"	66 3/4"	66 3/4"	66 3/4"	66 3/4"	66 3/4"
2060	2460	2660	2860	3060	3660	
6'-5 1/2"	6'-5 1/2"	6'-5 1/2"	6'-5 1/2"	6'-5 1/2"	6'-5 1/2"	6'-5 1/2"
6'-6"	6'-6"	6'-6"	6'-6"	6'-6"	6'-6"	6'-6"
1981	1981	1981	1981	1981	1981	1981
72 3/4"	72 3/4"	72 3/4"	72 3/4"	72 3/4"	72 3/4"	72 3/4"
2066	2466	2666	2866	3066	3666	
6'-11 1/2"	6'-11 1/2"	6'-11 1/2"	6'-11 1/2"	6'-11 1/2"	6'-11 1/2"	6'-11 1/2"
7'-0"	7'-0"	7'-0"	7'-0"	7'-0"	7'-0"	7'-0"
2133	2133	2133	2133	2133	2133	2133
78 3/4"	78 3/4"	78 3/4"	78 3/4"	78 3/4"	78 3/4"	78 3/4"
2070	2470	2670	2870	3070	3670	
7'-5 1/2"	7'-5 1/2"	7'-5 1/2"	7'-5 1/2"	7'-5 1/2"	7'-5 1/2"	7'-5 1/2"
7'-6"	7'-6"	7'-6"	7'-6"	7'-6"	7'-6"	7'-6"
2286	2286	2286	2286	2286	2286	2286
84 3/4"	84 3/4"	84 3/4"	84 3/4"	84 3/4"	84 3/4"	84 3/4"
2076	2476	2676	2876	3076	3676	



For jamb leg heights subtract leg drop from height

■ Shaded units meet or exceed egress opening requirements per 2015 IBC (International Building Code) minimum dimensions of 20" [508mm] clear opening width, 24" [610mm] clear opening height, 5.7 sq. ft. [5295cm²] clear opening and floor to bottom of clear opening not to exceed 44" [1118mm] in height.

Verify local or state egress opening sizes with your local building inspector.

Floor to bottom of clear opening dimensions are based on 82" [2083mm] jamb height of Weather Shield French doors and center hinged French doors.

See Opening Specification chart for reference.

Push-out casements only available up to 7-0

NOTE: Also available in 8-0 height

NOTE: Available hinged left, right or stationary.