

# Contemporary Collection™

# WEATHER SHIELD.

## Opening Specifications

## WINDOWS & DOORS

Bi-Fold Window (8623)

Revised 11/14/17

	Unit Code	Sq. Ft. Clear Opening / Vent			Clear Opening				Sq. Ft. DLO 3-1/4" Rail	Floor to Bottom of Clear Opening <sup>a</sup>	Sq. Ft. Overall Unit Area <sup>b</sup>
		Std. Sill	ADA Sill	U-channel Sill	Width <sup>c</sup>	Height (Std Sill)	Height (ADA Sill)	Height (U-channel Sill)			
2 Panel Windows	6-1 x 3-0	15.27	15.71	15.74	63.05	34.88	35.88	35.94	11.68	43.25	20.52
	6-1 x 4-0	20.53	20.96	20.99	63.05	46.88	47.88	47.94	16.38	31.25	26.54
	6-1 x 5-0	25.78	26.22	26.25	63.05	58.88	59.88	59.94	21.08	19.25	32.56
	6-1 x 6-0	31.03	31.47	31.50	63.05	70.88	71.88	71.94	25.80	31.25	38.59
3 Panel Windows	9-0 x 3-0	22.55	23.20	23.24	93.12	34.88	35.88	35.94	17.52	43.25	30.40
	9-0 x 4-0	30.31	30.96	31.00	93.12	46.88	47.88	47.94	24.57	31.25	39.32
	9-0 x 5-0	38.07	38.72	38.76	93.12	58.88	59.88	59.94	31.62	19.25	48.25
	9-0 x 6-0	45.83	46.48	46.52	93.12	70.88	71.88	71.94	38.70	31.25	57.17
4 Panel Windows	11-11 x 3-0	30.74	31.63	31.68	126.95	34.88	35.88	35.94	23.36	43.25	40.28
	11-11 x 4-0	41.32	42.21	42.26	126.95	46.88	47.88	47.94	32.76	31.25	52.11
	11-11 x 5-0	51.90	52.78	52.84	126.95	58.88	59.88	59.94	42.16	19.25	63.93
	11-11 x 6-0	62.48	63.36	63.42	126.95	70.88	71.88	71.94	51.60	31.25	75.76
5 Panel Windows	14-10 x 3-0	38.03	39.12	39.18	157.01	34.88	35.88	35.94	29.20	43.25	50.16
	14-10 x 4-0	51.11	52.20	52.27	157.01	46.88	47.88	47.94	40.95	31.25	64.89
	14-10 x 5-0	64.19	65.28	65.35	157.01	58.88	59.88	59.94	52.70	19.25	79.62
	14-10 x 6-0	77.28	78.37	78.44	157.01	70.88	71.88	71.94	64.50	31.25	94.34
6 Panel Windows	17-8 x 3-0	45.37	46.67	46.75	187.33	34.88	35.88	35.94	35.04	43.25	60.04
	17-8 x 4-0	60.98	62.28	62.36	187.33	46.88	47.88	47.94	49.14	31.25	77.67
	17-8 x 5-0	76.59	77.89	77.97	187.33	58.88	59.88	59.94	63.24	19.25	95.30
	17-8 x 6-0	92.20	93.50	93.58	187.33	70.88	71.88	71.94	77.40	31.25	112.93
7 Panel Windows	20-7 x 3-0	53.56	55.10	55.19	221.16	34.88	35.88	35.94	40.88	43.25	69.93
	20-7 x 4-0	71.99	73.53	73.62	221.16	46.88	47.88	47.94	57.33	31.25	90.45
	20-7 x 5-0	90.42	91.96	92.05	221.16	58.88	59.88	59.94	73.78	19.25	110.98
	20-7 x 6-0	108.85	110.39	110.48	221.16	70.88	71.88	71.94	90.30	31.25	131.51
8 Panel Windows	23-6 x 3-0	61.75	63.53	63.64	254.99	34.88	35.88	35.94	46.72	43.25	79.81
	23-6 x 4-0	83.00	84.77	84.88	254.99	46.88	47.88	47.94	65.52	31.25	103.24
	23-6 x 5-0	104.25	106.02	106.13	254.99	58.88	59.88	59.94	84.32	19.25	126.67
	23-6 x 6-0	125.50	127.27	127.38	254.99	70.88	71.88	71.94	103.20	31.25	150.10

Requirements per 2015 IBC (International Building Code) minimum dimensions of 20" clear opening width, 24" clear opening height, 5.7 sq. ft. clear opening and floor to bottom of clear opening not to exceed 44".

<sup>a</sup> Floor to bottom of clear opening dimensions are for standard sill and based on 82" jamb height of a 6-10 door.

All units over 5-0 height are based off 106" jamb height for floor to clear opening dimension.

<sup>b</sup> Sq. Ft. Overall Unit Area is calculated on the jamb dimension for standard sill.

<sup>c</sup> Clear opening width is calculated with all panels open. Multiple operations may be required which may affect egress.

The requirements outlined above for the major US building codes can be modified by local jurisdictions. Therefore, it is important to check local codes in the areas in which the product is to be installed.