

## **WINDOWS & DOORS**

## Quick Spec Guide Weather Shield Series™ Direct Set (630)

SPECIFICATION	STANDARD FEATURES	OPTIONAL FEATURES
EXTERIOR FINISH	• Primed	<ul> <li>8 Standard Colors</li> <li>47 Designer Colors</li> <li>Custom Color</li> <li>No Prime/ No Fingerjoint</li> </ul>
EXTERIOR TRIM	Standard Brickmould     Standard Subsill	<ul> <li>Washington K Style</li> <li>Flat Casing (9 Back Bands)</li> <li>Franklin Casing</li> <li>Beaded Casing (9 Back Bands)</li> <li>Stepped Casing (9 Back Bands)</li> <li>Stepped Casing (9 Back Bands)</li> <li>Subsill (9519)</li> <li>Subsill (9521)</li> <li>Subsill (9524)</li> </ul>
INTERIOR FINISH	Natural	<ul> <li>Clear Satin</li> <li>Fruitwood</li> <li>Primed</li> <li>Prefinished White &amp; Black</li> <li>Golden Oak</li> <li>Chestnut</li> <li>Poly – 12 Standard / 45</li> <li>Designer</li> </ul>
INTERIOR SPECIES	• Pine	Oak
SHAPE/SIZE	Shapes available include, Diamond, Eyebrow, Eyebrow w/ legs, Flat Top Pentagon, Flat Top Trapezoid, Full Circle, Gothic, Gothic w/ legs, Half Circle, Half Circle w/ legs, Hexagon, Octagon, Parallelogram, Pentagon, Quarter Circle, Quarter Circle w/ legs, Quarter Eyebrow, Quarter Eyebrow w/ legs, Rectangle, Right Triangle, Trapezoid, Triangle	<ul> <li>Custom jamb sizes from 9-1/2" to 120"</li> <li>Minimum Radius is 8-5/8"</li> <li>Minimum Corner Angle is 17 degrees</li> </ul>
GLAZING	Clear Insulated Glass	<ul> <li>Insulated Low E</li> <li>Insulated Low E 240</li> <li>Zo-E Shield 5</li> <li>Zo-E Shield 5</li> <li>Zo-E Shield 5 Extreme</li> <li>Zo-E Shield 6 (laminated)</li> <li>Zo-E Shield 7 (triple insul)</li> <li>Single Glaze</li> <li>Gray or Bronze Tint</li> <li>Obscure</li> <li>Tempered</li> </ul>
GRILLES		<ul> <li>GBG: 5/8" Flat or 11/16" Sculptured</li> <li>SDL: 5/8", 7/8", 1-3/8", 2"</li> <li>Wood Grille: 5/8", 7/8", 1-3/8"</li> </ul>
SASH		Casement Sash
JAMB	• 4-9/16"	• 4-9/16" Min • 12" Max